

Stainless Steel & Media Isolated Pressure Sensors Line Guide



Stainless products. Steeled expertise. Honeywell Sensing and Control (S&C) offers decades of experience in the stainless steel pressure transducers industry. That's why, industry-wide, our transducers are known for enhanced quality, reliability, and service – which adds up to outstanding value for your applications. Most Honeywell S&C transducers take advantage of piezoresistive technology, and are fully steel media isolating with

stainless steel or aerospace alloys and no internal elastometric seals. This design often makes them resistant to harsh, aggressive media and challenging environments. What's more, long before they're shipped, our transducers are tested against critical manufacturing specifications. Then again, you expect meticulous attention to detail from an industry leader.

FEATURES

STAINLESS STEEL & MEDIA ISOLATED PRESSURE SENSORS SA Series.

Features: Sealed construction • Wide choice of pressure ranges • UL approved • Reverse polarity protection • RFI/EMI protection • PSIG, PSIS, and PSIA versions • Amplified and temperature compensated • Calibrated and compensated • Field interchangeable

Benefits: Water-resistant, rugged, stainless steel case for protection from harsh environments. Internal hermetic sealing provides measurement of absolute pressures or those referenced to a sealed chamber. Approved by Underwriters Laboratories as a component in float and pressure-operated motor controller. Potential applications include freon and ammonia refrigerant monitoring in HVAC/R systems, hydraulic controls, blood diffusion, agriculture sprayers and dusters, compressors, engine controls, energy management systems, robotics, automated machining, automotive systems, and general industrial pressure monitoring/control systems.

DG Series.

Features: Meets SAE J1211 specifications for under hood applications • High

temperature capability [125 °C, 257 °F]

• Wide choice of pressure ranges (100 psis to 7000 psis) • Integral automotive type connector • Reverse polarity and output protection • Ratiometric output • Sealed steel case • Amplified and temperature compensated • Enhances installation

Benefits: Steel case seals internal electronics from environment for enhanced reliability in tough, hostile environments. Output can interface directly with many microprocessors with onboard A/D converters, reducing typical transducer support circuitry. Potential applications include automotive brake systems, fuel rail/injection engine oil, continuously variable transmissions, active suspensions, and energy management.

Eclipse Series.

Features: Voltage or current output • Broad selection of ranges • CE, UL, and cUL listings for some combinations • Weatherproof-type connector • IP65 sealed case with appropriate connector • IP66 with cable termination • Often suitable for marine or off-road vehicle use • Internal signal amplification • Low-excitation voltage • Reverse polarity protection

Benefits: Designed for high volume OEMs requiring a low-cost pressure transmitter for industrial and heavy-duty applications. Rugged packaging and plated steel case provide environmental protection for electronics. Output in mA useful for applications with high RFI/EMI electrical noise. Potential applications include automotive systems, hydraulic/pneumatic controls, air compressors, energy management (compressors, refrigeration/chiller control), process control systems, and engine controls and monitors.

BL Series.

Features: Flush diaphragm • Hermetically sealed • Easily cleaned/adaptable • FM approval • Accuracies to 0.25 % • Measures vacuum • Reverse polarity protection • Amplified 4 to 20 mA output and temperature compensated

Benefits: Flush diaphragm suited to measuring viscous fluids, slurries, and media where system flushing is necessary. May be mounted in an adapter. Factory Mutual approval as an intrinsically safe device when used with approved barriers for use in hazardous areas. Potential applications include depth sensing,

Stainless Steel & Media Isolated Pressure Sensors Line Guide

When reliability is demanded, Honeywell delivers.

Stainless steel pressure transducers are found in applications where sensors cannot be easily replaced — where supreme durability is a top priority. That's why you'll find Honeywell S&C pressure transducers performing expertly in potential applications, such as compressors and hydraulic controls, and in industries as diverse as aerospace, medical, transportation, agriculture, refrigeration, and industrial. Our full line of sensors deliver enhanced performance and reliability, plus: bonded strain gage technology enhances resistance to shock, vibration and hostile conditions; absolute, gage and sealed-gage measurement; a wide array of pressure ranges, port styles, termination types, and outputs; package types from miniature surface mount sensors to high-end stainless steel isolated transmitters (for stringent process control); pressure ranges from 3 psi to 20k psi; and corrosion resistance.



Pressure Sensors

	SA Series	DG Series
Pressure connection	1/8-27 NPT, 3/8-24 UNF, PT-1/4	3/8-24 UNF
Measurement type	absolute, gage, sealed gage	sealed gage
Construction	wetted parts 304/306 SS housing	wetted parts 304/306 SS housing
Pressure range	0 psi to 7000 psi (inclusive)	0 bar to 35 bar (inclusive) 0 psi to 7100 psi (inclusive)
Output signal	1 Vdc to 6 Vdc	0.25 Vdc to 4.75 Vdc
Accuracy	1.0 % full scale BFSL	1.0 % full scale BFSL
Amplified	yes	yes
Compensated temperature range	-1 °C to 85 °C [30 °F to 185 °F] (compensated)	-40 °C to 125 °C [-40 °F to 257 °F] (compensated)
Termination	Hirschmann connector, 3-conductor shielded cable	Packard Metri-Pack



Pressure Sensors

	Eclipse Series	BL Series
Pressure connection	1/8-27 NPT, G1/4 BSP	flush diaphragm
Measurement type	gage, sealed gage	absolute, gage, sealed gage
Construction	wetted parts 304/306 SS housing	wetted parts 15-5 PH/316L SS
Pressure range	0 bar to 500 bar (inclusive), 0 psi to 7100 psi (inclusive)	0 psi to 20000 psi (inclusive)
Output signal	0.5 Vdc to 4.5 Vdc, 4 mA to 20 mA	4 mA to 20 mA
Accuracy	0.25 % full scale BFSL	0.25 % to 1 % full scale BFSL (inclusive)
Amplified	yes	yes
Compensated temperature range	-1 °C to 82 °C [30 °F to 180 °F] (compensated)	-1 °C to 54 °C [30 °F to 130 °F]
Termination	Hirschmann connector, Packard Metri-Pack and connector	Bendix connector



Pressure Sensors


	Datamate Series	XPRO Series
Pressure connection	1/8-27 NPT	1/8-27 NPT, 3/8-24 UNF, PT-1/4
Measurement type	gage, sealed gage	absolute, gage, sealed gage
Construction	300 SS	wetted parts 304/306 SS housing
Pressure range	0 psi to 5000 psi (inclusive)	0 psi to 7000 psi (inclusive)
Output signal	4 mA to 20 mA	4 mA to 20 mA
Accuracy	1.0 % full scale BFSL	1.0 % full scale BFSL
Amplified	yes	yes
Compensated temperature range	-1 °C to 54 °C [30 °F to 130 °F]	-1 °C to 85 °C [30 °F to 185 °F]
Termination	3 Wire 24 AWG, 1/2 in NPT conduit	Hirschmann connector, 3-conductor shielded cable



Pressure Sensors

	MLH Series
Pressure connection	1/4-18 NPT, M12 x 1.5 (ISO 6149), M14 x 1.5 (ISO 6149), 3/8-24 UNF (SAE-3 O-ring boss), M18 x 1.5 (ISO 6149), 1/8 in-27 NPT, 1/2 in-20 UNF (SAE-5 O-ring boss), M10 x 1 (ISO 6149), 1/4 in SAE Female Schrader, 7/16-20 UNF (SAE-4 O-ring boss), 1/2 in NPT, 9/16-18 UNF (SAE-6 O-ring boss), PT 1/4-19 BSP Tapered Thread, G 1/4-19 (DIN 3852-2), G 1/8 with O-ring groove, M16 x 1.5 (ISO 6149), G 1/4 with O-ring groove, G 1/8 (DIN 3852-2), PT1/8-28 BSP Tapered Thread, M20 x 1.5 (ISO 6149), 1/2-20 37° Flare (SAE JIC)
Measurement type	gage, sealed gage
Construction	all wetted parts equivalent to 300 SS
Pressure range	50 psi to 8000 psi (inclusive)
Output signal	0.5 Vdc to 4.5 Vdc ratiometric output from 5 Vdc excitation, 4 mA to 20 mA current from 9.5 Vdc to 30 Vdc excitation, 1.0 Vdc to 6.0 Vdc regulated output from 8 Vdc to 30 Vdc excitation, 0.25 Vdc to 10.25 Vdc regulated output from 14 Vdc to 30 Vdc excitation, 0.5 Vdc to 4.5 Vdc regulated output from 7 Vdc to 30 Vdc excitation, 0 mV to 50 mV from 5 Vdc excitation, 1 Vdc to 5 Vdc output from 8 Vdc to 30 Vdc excitation
Accuracy	±0.25 % full scale BFSL
Amplified	yes
Compensated temperature range	-40 °C to 125 °C [-40 °F to 257 °F]
Termination	Packard MetriPak 150, Hirschmann, M12 x 1 (Brad Harrison micro), DIN 72585 (Cannon APD type), DIN 43650-C (IP65), Amp Superseal 1.5 (IP67), cable, flying leads, Deutsch DTM04-3P (integral)

Stainless Steel & Media Isolated Pressure Sensors Line Guide



13 mm Series



19 mm Series



SPT Series

Pressure Sensors

Pressure connection	ring with back support, 1/8-27 NPT, 1/4-18 NPT, 7/16 UNF	cell with body O-ring, flush mount, flush mount with flange, 1/8-27 NPT, 1/4-18 NPT, 7/16 UNF, 1/4 BSPP, Euro O-ring, 1/4 VCR (female nut)	1/8-27 NPT, 1/4-18 NPT, 7/16-20 UNF, 1/4-19 BSPP, 1/4 VCR gland
Measurement type	absolute, sealed gage	absolute, gage, vacuum gage	absolute, gage, sealed gage, vacuum gage pressures
Construction	wetted parts 316 L SS	wetted parts 316 L SS	wetted parts 316 L SS housing
Pressure range	0 psi to 5000 psi (inclusive)	0 psi to 500 psi (inclusive)	0 psi to 5000 psi (inclusive)
Output signal	10 Vdc excitation, 1.5 mA excitation	10 Vdc excitation, 1.5 mA excitation	4 mA to 20 mA, 0 mV to 100 mV, 1 Vdc to 5 Vdc
Accuracy	100 mV (nominal) linearity and hysteresis 0.2 % typ.	100 mV (nominal) linearity and hysteresis 0.2 % max.	0.25 % max.
Amplified	no	no	yes, amplified and unamplified
Compensated temperature range	0 °C to 82 °C [32 °F to 180 °F]	0 °C to 82 °C [32 °F to 180 °F]	-10 °C to 85 °C [14 °F to 185 °F]
Termination	pins, ribbon cable	ribbon cable	bayonet connector, cable



AB/HP Series



MM Series



SR Series

Pressure Sensors

Pressure connection	flush diaphragm	1/8-27 NPT, 3/8-24 UNF, G 1/8 BSP, G 1/4 BSP	capsule
Measurement type	sealed gage	gage	gage
Construction	316L or 15-5PH stainless steel	wetted parts, 304/306 SS housing	wetted parts 304/306 SS housing
Pressure range	0 psi to 20000 psi (inclusive)	0 psi to 7000 psi (inclusive)	0 psi to 2000 psi (inclusive)
Output signal	0 mV to 100 mV	0 mV to 50 mV	25 mV/mA
Accuracy	0.5 % full scale BFSL, 0.25 % full scale BFSL	0.5 % full scale BFSL, 0.25 % full scale BFSL	1 % full scale BFSL
Amplified	no	no	no
Compensated temperature range	-1 °C to 71 °C [30 °F to 160 °F]	-1 °C to 82 °C [30 °F to 180 °F]	0 °C to 75 °C [32 °F to 167 °F]
Termination	4-conductor shielded cable (various lengths), Bendix high temperature connector	Hirschmann connector, Hollingsworth connector	pin



Pressure Sensors

BX Series

EA Series

	BX Series	EA Series
Pressure connection	flush diaphragm	1/4 tube, 1/8-27 NPT, 3/8-24 UNF
Measurement type	gage	gage
Construction	wetted parts 304/306 SS housing	wetted parts 304/306 SS housing
Pressure range	0 psi to 300 psi (inclusive)	0 psi to 5000 psi (inclusive)
Output signal	0 mVdc to 50 mVdc	1 Vdc to 6 Vdc
Accuracy	1 % full scale BFSL	1 % full scale BFSL
Amplified	no	yes
Compensated temperature range	0 °C to 80 °C [32 °F to 176 °F]	-1 °C to 85 °C [30 °F to 185 °F]
Termination	pin	quick disconnect

water resource management, process controls, marine instrumentation, chemical manufacture, tank/liquid level, and paint spraying applications. May also potentially be used in food & beverage, pulp & paper, and petro-chemical industries.

Datamate Series.

Features: Conduit connections for process industry • Waterproof exterior • Factory calibration • Designed to be intrinsically safe • Wide choice of pressure ranges • Reverse polarity protected • Amplified and temperature compensated

Benefits: Two-wire pressure transmitter compatible with data loggers and instrumentation used in processing environments. 4 mA to 20 mA output for remote monitoring of primary and secondary process variables. Threaded connector allows conduit to be easily attached. Often suitable for use with media in potential applications that would otherwise require isolators such as liquid level measurement, plant utilities, gas transmission pipeline, flow detection, geophysical monitoring, and lubrication.

XPRO Series.

Features: Sealed, rugged package • 1 % accuracy for secondary process measurements • Low cost • Stainless steel • Designed to be intrinsically safe • Corrosion resistant • Often suited for industrial environments • Amplified and temperature compensated

Benefits: 4 mA to 20 mA output suited for long cable-runs in electrically noisy environments. Silicon strain gages mounted on a beam coupled to stainless steel diaphragm for maximum isolation from thermal transients. Stainless steel pressure cavity has no elastomer seals or adhesive bonds to corrode. Designed to be intrinsically safe for use in hazardous locations when used with approved barriers. Potential applications include freon and ammonia refrigeration, process control, flow detection, pneumatic systems, water resource management, and liquid level measurement.

MLH Series.

Features: All-wetted parts • No internal elastomeric seals • Stable and creep free • Reverse voltage and output short circuit protected • Less than 2ms response time • Easy customization • Rated IP65 or better • Exceeds CE heavy industrial EMC for use in areas of high RFI/EMI • Amplified and temperature compensated • Wide choice of connections and terminations • Calibration for special pressure ranges

Benefits: Combines ASIC technology with media isolated, metal diaphragm. All metal wetted parts for use in a variety of potential fluid applications. Amplified outputs often eliminate cost of external amplifiers. Wide selection of industry standard connectors and process ports for enhanced reliability and user flexibility. Potential applications include diesel engines, refrigeration and HVAC/R, general industrial and hydraulics, off-road vehicles, braking systems, natural gas vehicles, and medical.

13 mm Series.

Features: Rugged, isolated stainless steel package • Accommodates media that will not adversely affect 316 stainless steel • Often reliable semiconductor technology • Calibrated and temperature compensated • Voltage or current supply options • Absolute and sealed gage pressures • For potential applications from 500 psi to 5,000 psi

Benefits: Used in high pressure potential applications involving measurement of hostile media in harsh environments. Piezoresistive semiconductor sensor chip in oil-isolated housing with or without an integral ceramic for temperature compensation and calibration is designed to provide reliable, stable, and accurate performance. Weld-ring collar and special back support ring for enhanced cycle life capability as well as further package integration in OEM applications. Potential applications include industrial and hydraulic controls, tank pressure, pressure transmitters, and process control systems.

19 mm Series.

Features: Rugged, isolated stainless steel package • Accommodates media that will not adversely affect 316 stainless steel • Small size • Often reliable semiconductor technology • Absolute and gage pressures • Vacuum compatible, isolated sensors • Calibrated and temperature compensated (some listings) • For potential applications up to 500 psi

Benefits: Variety of pressure connections allow use in wide range of OEM equipment. Uncompensated version for use in potential applications using specialized circuit designs. Rugged and often reliable for use in potential applications where corrosive liquids or gases are monitored and may also be exposed to a vacuum such as industrial controls, process control systems, industrial automation and flow control, and pressure calibrators.

SPT Series.

Features: Often reliable semiconductor technology • Rugged, 316 stainless steel wetted parts • Calibrated and temperature compensated • NEMA 4 design • Absolute, gage, sealed gage, and vacuum gage pressures • Often ideal for potential applications where medial compatibility is a problem

Benefits: Variety of pressure connections allows use in wide range of OEM equipment. For use in potential applications where corrosive liquids and gases are monitored such as industrial automation and flow control, pressure instrumentation, hydraulic systems, and process control.

AB/HP Series.

Features: Flush-mount • Many mounting options • Easy to clean • Enhanced accuracy • Two thermally matched strain gages • PSIA and bi-directional models • Applicable to special packaging • Temperature compensated and calibrated

Benefits: Flush-mounted for use in potential applications where ease of cleaning or low-fluid volumes are

important requirements. May also be mounted in adapter for more conventional installations. Both zero and full-scale temperature compensation are held to extremely narrow limits. Potential applications include respirators, fire fighting equipment, drilling mud density, kidney dialysis machines, hydraulic servo valves, gas monitoring, transit vehicle braking systems, liquid-level measurement, landing gear hydraulic pressure, geophysical research, engine monitor control, and diesel engines.

MM Series.

Features: Low cost • Wide choice of pressure ranges • Rugged, compact configuration • Corrosion resistant • PC mountable • Threaded port • No adapter required • Easy to package • Temperature compensated

Benefits: Rugged construction and proven reliability. Fully compensated and completely interchangeable without further calibration. Used with a wide variety of corrosive media such as ammonia, water, and hydraulic fluids in gas chromatography, paint-spraying systems, electronic pressure switches, medical diagnostics, heat pumps, hydraulic controls, irrigation systems, and automotive.

SR Series.

Features: Low cost • High-impedance silicon strain gages • Small size • Stainless steel • Low-current draw • Enhanced reliability • Enhanced corrosion resistance • Wide range of pressure measurements • Constant current excitation • Temperature compensated

Benefits: Low current draw allows use with batteries. Sensing elements isolated from media. Provides high working pressures, high overload and burst pressures often at no additional cost. Temperature compensated to improve system performance often at no additional cost, unlike other low cost sensors. Works with readily available 4 mA to 20 mA amplifier ICs. Potential applications include pressure transducers, “smart” valves, solid-state pressure switches, and pressure transmitters.

BX Series.

Features: Low cost • Small size • Oil-free isolated sensor • Flush-mount, non-corrugated diaphragm • High-impedance • Constant current • Temperature compensated

Benefits: Enhanced performance, calibrated, and temperature compensated. Small size often ideal for portable equipment. Stainless steel construction designed to tolerate a wide variety of corrosive media. Small, flush mount diaphragm often ideal for medical, beverage, and food processing potential applications where stringent sanitation requirements are necessary. Other potential applications include pressure transmitters, solid-state pressure switches, “smart” valves, and OEM medical equipment.

EA Series.

Features: Large choice of pressure ranges • UL approval • Rugged, lightweight Valox case • Compatible with microprocessors • Amplified and temperature compensated • Corrosion resistance

Benefits: Pressure port, amplifier, and voltage supply-regulator packaged in Valox case. Operates through millions of pressure cycles without damage and is well suited for cycling regimes. Potential applications include agricultural sprayers, air conditioning, refrigeration, engine controls, environmental control systems, compressors, hydraulic and pneumatic controls, robotics, transmissions, and waste management.

Warranty. Honeywell warrants goods of its manufacture as being free of defective materials and faulty workmanship. Honeywell's standard product warranty applies unless agreed to otherwise by Honeywell in writing; please refer to your order acknowledgement or consult your local sales office for specific warranty details. If warranted goods are returned to Honeywell during the period of coverage, Honeywell will repair or replace, at its option, without charge those items it finds defective. **The foregoing is buyer's sole remedy and is in lieu of all warranties, expressed or implied, including those of merchantability and fitness for a particular purpose. In no event shall Honeywell be liable for consequential, special, or indirect damages.**

While we provide application assistance personally, through our literature and the Honeywell web site, it is up to the customer to determine the suitability of the product in the application.

Specifications may change without notice. The information we supply is believed to be accurate and reliable as of this printing. However, we assume no responsibility for its use.

For more information about Sensing and Control products, visit www.honeywell.com/sensing or call +1-815-235-6847. Email inquiries to info.sc@honeywell.com

 **WARNING**
PERSONAL INJURY

- DO NOT USE these products as safety or emergency stop devices or in any other application where failure of the product could result in personal injury.

Failure to comply with these instructions could result in death or serious injury.

 **WARNING**
MISUSE OF DOCUMENTATION

- The information presented in this catalogue is for reference only. DO NOT USE this document as product installation information.
- Complete installation, operation and maintenance information is provided in the instructions supplied with each product.

Failure to comply with these instructions could result in death or serious injury.

Sensing and Control
Automation and Control Solutions
Honeywell
1985 Douglas Drive North
Golden Valley, MN 55422 USA
+1-815-235-6847
www.honeywell.com/sensing

008154-1-EN IL50 GLO
June 2008
Copyright © 2008 Honeywell International Inc. All rights reserved.

Honeywell